





	WLL (working load limit) i ton											
	Enpartigt						Tvåpartigt				Tre-och fyrpartigt	
												
ß							0°-45°	45°-60°	0°-45°	45°-60°	0°-45°	45°-60°
Faktor	1	2	0,8	1,6	2	4	1,4	1	1,4	1	2,1	1,5
Dim.mm	Belastningstabell ställinor 1770 N/mm ² . Fiberkärna. Säkerhetsfaktor 5:1											
3	0,09	0,18	0,07	0,14	0,18	0,36	0,12	0,09	0,12	0,09	0,19	0,13
4	0,15	0,3	0,12	0,24	0,3	0,6	0,21	0,15	0,21	0,15	0,31	0,22
5	0,25	0,5	0,20	0,40	0,5	1,0	0,35	0,25	0,35	0,25	0,53	0,38
6	0,35	0,7	0,28	0,56	0,7	1,4	0,49	0,35	0,49	0,35	0,74	0,53
8	0,7	1,4	0,55	1,1	1,4	2,8	0,95	0,7	0,95	0,7	1,5	1,05
10	1,05	2,1	0,85	1,7	2,1	4,2	1,5	1,05	1,5	1,05	2,25	1,6
12	1,55	3,1	1,2	2,5	3,1	6,2	2,12	1,55	2,12	1,55	3,3	2,3
14	2,12	4,2	1,7	3,3	4,2	8,4	3,0	2,12	3,0	2,12	4,35	3,15
16	2,7	5,4	2,2	4,35	5,4	10,8	3,85	2,7	3,85	2,7	5,65	4,2
18	3,4	6,8	2,7	5,65	6,8	13,6	4,8	3,4	4,8	3,4	7,2	5,2
20	4,35	8,7	3,4	6,9	8,7	17,4	6,0	4,35	6,0	4,35	9,0	6,5
22	5,2	10,4	4,1	8,4	10,4	20,8	7,2	5,2	7,2	5,2	11,0	7,8
24	6,3	12,6	5,0	10,0	12,6	25,2	8,8	6,3	8,8	6,3	13,5	9,4
26	7,2	14,4	5,8	11,8	14,4	28,8	10,0	7,2	10,0	7,2	15,0	11,0
28	8,4	16,8	6,7	13,5	16,8	33,6	11,8	8,4	11,8	8,4	18,0	12,5
32	11,0	22,0	8,8	18,0	22,0	44,0	15,0	11,0	15,0	11,0	23,5	16,5
36	14,0	28,0	11,2	22,5	28,0	56,0	19,0	14,0	19,0	14,0	29,0	21,0
40	17,0	34,0	13,6	28,0	34,0	68,0	23,5	17,0	23,5	17,0	36,0	26,0
44	21,0	42,0	16,8	33,5	42,0	84,0	29,0	21,0	29,0	21,0	44,0	31,5
48	25,0	50,0	20,0	40,0	50,0	100,0	35,0	25,0	35,0	25,0	52,0	37,0
52	29,0	58,0	23,2	47,0	58,0	116,0	40,0	29,0	40,0	29,0	62,0	44,0
56	33,5	67,0	26,8	54,0	67,0	134,0	47,0	33,5	47,0	33,5	71,0	50,0
60	39,0	78,0	31,2	63,0	78,0	156,0	54,0	39,0	54,0	39,0	81,0	58,0