





	WLL (working load limit) i ton											
	Enpartigt						Tvåpartigt				Tre-och fyrpartigt	
												
ß							0°-45°	45°-60°	0°-45°	45°-60°	0°-45°	45°-60°
Faktor	1	2	0,8	1,6	2	4	1,4	1	1,4	1	2,1	1,5
Dim.mm	Belastningstabell stållinor 1960 N/mm ² . Stålkärna. Säkerhetsfaktor 5:1											
8	0,8	1,6	0,65	1,3	1,6	3,2	1,15	0,8	1,15	0,8	1,7	1,2
10	1,3	2,6	1,05	2,1	2,6	5,2	1,8	1,3	1,8	1,3	2,7	1,95
12	1,8	3,6	1,45	2,9	3,6	7,2	2,5	1,8	2,5	1,8	3,8	2,7
14	2,5	5,0	2,0	4,0	5,0	10,0	3,5	2,5	3,5	2,5	5,3	3,8
16	3,3	6,6	2,6	5,3	6,6	13,2	4,7	3,3	4,7	3,3	6,9	5,0
18	4,1	8,2	3,3	6,6	8,2	16,4	5,8	4,1	5,8	4,1	8,6	6,2
20	5,1	10,2	4,1	8,2	10,2	20,4	7,2	5,1	7,2	5,1	10,7	7,7
22	6,2	12,4	5,0	9,9	12,4	24,8	8,7	6,2	8,7	6,2	13,0	9,3
24	7,4	14,8	5,9	11,8	14,8	29,6	10,4	7,4	10,4	7,4	15,5	11,1
26	8,7	17,4	7,0	13,9	17,4	34,8	12,3	8,7	12,3	8,7	18,3	13,1
28	10,0	20,0	8,0	16,0	20,0	40,0	14,1	10,0	14,1	10,0	21,0	15,0
32	13,0	26,0	10,4	20,8	26,0	52,0	18,3	13,0	18,3	13,0	27,3	19,5