





 ß	WLL = Arbetslast(working load limit) i ton										
	Enpartigt					Tvåpartigt				Tre- och fyrpartiga	
											
			Parallell	0°-45°	45°-60°	0°-45°	45°-60°	0°-45°	45°-60°	0°-45°	45°-60°
Faktor	1	0,8	2	1,4	1,0	0,7	0,5	1,4	1	2,1	1,5
	1,0	0,8	2,0	1,4	1,0	0,7	0,5	1,4	1,0	2,1	1,5
	2,0	1,6	4,0	2,8	2,0	1,4	1,0	2,8	2,0	4,2	3,0
	3,0	2,4	6,0	4,2	3,0	2,1	1,5	4,2	3,0	6,3	4,5
	4,0	3,2	8,0	5,6	4,0	2,8	2,0	5,6	4,0	8,4	6,0
	5,0	4,0	10,0	7,0	5,0	3,5	2,5	7,0	5,0	10,5	7,5
	6,0	4,8	12,0	8,4	6,0	4,2	3,0	8,4	6,0	12,6	9,0
	8,0	6,4	16,0	11,2	8,0	5,6	4,0	11,2	8,0	16,8	12,0
	10,0	8,0	20,0	14,0	10,0	7,0	5,0	14,0	10,0	21,0	15,0
	12,0	9,6	24,0	16,8	12,0	8,4	6,0	16,8	12,0	25,2	18,0
	15,0	12,0	30,0	21,0	15,0	10,5	7,5	21,0	15,0	31,5	22,5
	20,0	16,0	40,0	28,0	20,0	14,0	10,0	28,0	20,0	42,0	30,0
	30,0	24,0	60,0	42,0	30,0	21,0	15,0	42,0	30,0	63,0	45,0