






	WLL (working load limit) i ton									
	Enpartigt				Tvåpartigt				Tre-och fyrpartigt	
										
ß	0°	0°	0°-45°	45°-60°	0°-45°	45°-60°	0°-45°	45°-60°	0°-45°	45°-60°
Faktor	1	0,8	1,4	1	1,4	1,0	1,12	0,8	2,1	1,5
Dim. mm	Belastningstabell kättingredskap klass 8									
5	0,8	0,64	1,12	0,8	1,12	0,8	0,9	0,64	1,6	1,18
6	1,12	0,90	1,6	1,12	1,6	1,12	1,25	0,9	2,36	1,7
7	1,5	1,20	2,1	1,5	2,12	1,5	1,7	1,2	3,15	2,24
8	2,0	1,60	2,8	2,0	2,8	2,0	2,24	1,6	4,25	3,0
10	3,15	2,50	4,25	3,15	4,25	3,15	3,55	2,5	6,7	4,75
13	5,3	4,25	7,5	5,3	7,5	5,3	5,9	4,25	11,2	8,0
16	8,0	6,30	11,2	8,0	11,2	8,0	9,0	6,3	17,0	11,8
19	11,2	8,95	16,0	11,2	16,0	11,2	12,5	8,95	23,6	17,0
20	12,5	10,0	17,0	12,5	17,0	12,5	14,0	10,0	26,5	19,0
22	15,0	12,0	21,2	15,0	21,2	15,0	17,0	12,0	31,5	22,4
26	21,2	17,0	30,0	21,2	30,0	21,2	23,7	17,0	45,0	31,5
32	31,5	25,2	45,0	31,5	45,0	31,5	35,2	25,2	67,0	47,5